



SPECIFICATION SHEET

TANK - FLEX



FIREQUIP TANK - FLEX CONVENTIONAL HARD RUBBER WIRE REINFORCED SUCTION HOSE

CONSTRUCTION

- OUTER JACKETS (COVER AND TUBE) MADE OF SYNTHETIC EPDM RUBBER
- LINER HAS A SPECIAL WIRE HELIX AND NYLON FABRIC REINFORCEMENT
- CONSTRUCTED WITH SOFT CUFF ENDS FOR GREATER COUPLING RETENTION
 - SMOOTH COVER AND INNER LINER
 - 10 FOOT STANDARD LENGTHS

APPLICATIONS

- DRAFTING FROM ANY RURAL OR MUNICIPAL NON-PRESSURIZED WATER SOURCE
- DESIGNED SPECIFICALLY FOR RURAL FIRE DEPARTMENTS EASE OF HANDLING
 - MUNICIPAL WATER SUPPLY TRANSFER

PERFORMANCE FEATURES

- MORE FLEXIBLE THAN MOST STANDARD HARD SUCTION HOSE FOR EASIER AND FASTER HOOKUP
 - TOUGH AND DURABLE – CAN WITHSTAND PRESSURE IF REQUIRED
 - DESIGNED FOR FULL VACUUM
 - OZONE RESISTANT
 - NO PLASTIC COUPLINGS
 - MEETS OR EXCEEDS NFPA STANDARD 1961, CURRENT EDITION
 - FIVE YEAR WARRANTY

FIREQUIP TANK-FLEX PERFORMANCE AND WEIGHT CHART

Hose Size	Bowl Size	Working Pressure PSI	Burst PSI	Weight per 10ft Length (uncoupled)
2 1/2 "	3 "	150	450	16
3 "	3-9/26 "	150	450	20
4 "	4-5/8 "	150	450	28
4 1/2 "	5-3/8 "	165	495	39
5 "	5-7/8 "	165	495	43
6 "	6-7/8 "	165	495	58

Website: www.firequip.com • Mailing Address: P.O. Box 2598 Burlington, NC 27216

Toll Free 1-800-334-6823 • Phone: 336-227-0123