

# 1" Assault Nozzle with or without Pistol Grip

## STYLE 4802

Assault Nozzles combine quality stream performance at a variety of pressures with the simplicity of a fixed orifice. Quality stream performance at a variety of pressures, combined with a durable and simple design makes it an unbeatable value. This product has a variety of applications. For use as deicing nozzles or in firefighting, mining or specialty vehicle applications, the Assault Nozzle is versatile and durable.



[Pair with a handline nozzle shutoff and ergonomic pistol grip. Choose from several "snap-on" grip and handle colors to help identify pre-connects and better manage inventory.](#)

Find a distributor near you for more information.

## Features

The Assault provides:

- Better stream performance at pressures as low as 50 PSI
- Affordably priced
- Simplified nozzle training
- No recalibration required
- Low maintenance due to simple, durable design
- Pattern Identification
- Larger easy to read labels
- Easy to operate (1/4 turn from straight stream to fog)
- Raised lug marks straight stream for limited visibility operations
- Easy to service & repair
- Meets European Standard
- Quick change pattern adjustment
- 100 psi (7 bar), optional 6 bar available. Maximum hydrostatic pressure PN40 or 580 psi.
- Compatible with Quick-Attack Foam Tube Style 790
- Nozzle comes with Spinning Teeth
- 13, 25, or 40 gpm (50, 100, or 150 lpm) \*Must specify flow option GPM (230 LPM) flow
- Swivel 1" (25 mm) Inlet
- 8 15/16" (227 mm) Long
- 3 1/4 lbs. (1.5 kg.)

## Applications/Solutions

- Firefighting - Structural

## Specifications

Style	4802
Certification(s)	 
Warranty	
Weight	3 1/4 lbs (1.5 kg)
Type	Fixed Orifice
Material	Pyrolite
Brand	Assault
Swivel Inlet	1" (25 mm)
Length	8 15/16" (227 mm)
Flow (GPM)	12, 25, 40 @ 100 PSI
Flow (LPM)	50, 100, 150 @ 7 BAR

