

“The Best Hose Suspension in the World”



MODEL  
**HB 100 ED**  
For  
**Hose I.D. 1” (2.5cm)**



Material:	<b>URETHANE</b>	
Length:	<b>16" / 40.6 cm</b>	
Shipping Weight:	<b>3 lbs / 1.4 kgs</b>	
Shipping Dimensions:	<b>21 x 8 x 4" / 53 x 21 x 10 cm</b>	
Sling Model:	<b>Metal "D-Ring" Sling</b>	
Sling Type:	<b>RS 16D</b>	
*Sling height:	<b>8" / 20 cm</b>	
Sling Material:	<b>UV Resistant Treated Polyester</b>	
Rated Capacity:	<b>1350 lbs/ 612 kgs @ 5:1 WLL</b>	<b>437 kgs/ 964 lbs @ 7:1 WLL</b>
Maximum Temperature:	<b>200° F / 93.3° C</b>	

\*Measured from top of the bun to the top of the sling

**Notes:** The most popular petroleum hose model Used throughout the world at refueling stations.  
Often used conjunction with retractors.

**CE certified slings available at a rated capacity of 500 kgs @ 7:1**

“The Best Hose Suspension in the World”



MODEL  
**HB 125 ED**

For  
**Hose I.D. 1<sup>1</sup>/<sub>4</sub>" (3.1cm)**



Material:	<b>URETHANE</b>	
Length:	<b>17.5" / 44.45 cm</b>	
Shipping Weight:	<b>3.5 lbs / 1.6 kgs</b>	
Shipping Dimensions:	<b>21 x 8 x 4" / 53.4 x 21 x 10 cm</b>	
Sling Model:	<b>Metal "D-Ring" Sling</b>	
Sling Type:	<b>RS 16D</b>	
*Sling height:	<b>7" / 17.8 cm</b>	
Sling Material:	<b>UV Resistant Treated Polyester</b>	
Rated Capacity:	<b>1350 lbs/ 612 kgs @ 5:1 WLL</b>	<b>437 kgs/ 964 lbs @ 7:1 WLL</b>
Maximum Temperature:	<b>200° F / 93.3° C</b>	

\*Measured from top of the bun to the top of the sling

**Notes:** Used with petroleum hose, refueling stations with hyhose retractors, hydraulic hose bundles and theatrical cabling.

**CE certified slings available at a rated capacity of 500 kgs @ 7:1**

**“The Best Hose Suspension in the World”**



**MODEL**

**HB 150 ED**

**For**

**Hose I.D. 1 1/2" (3.8cm)**



Material:	<b>URETHANE</b>	
Length:	<b>19.5" / 49.5 cm</b>	
Shipping Weight:	<b>4 lbs / 1.8 kgs</b>	
Shipping Dimensions:	<b>21 x 8 x 4" / 53 x 21 x 10 cm</b>	
Sling Model:	<b>Metal "D-Ring" Sling</b>	
Sling Type:	<b>RS 16D</b>	
*Sling height:	<b>6.5" / 16.5 cm</b>	
Sling Material:	<b>UV Resistant Treated Polyester</b>	
Rated Capacity:	<b>1350 lbs/ 612 kgs @ 5:1 WLL</b>	<b>437 kgs/ 964 lbs @ 7:1 WLL</b>
Maximum Temperature:	<b>200° F / 93.3° C</b>	

\*Measured from top of the bun to the top of the sling

**Notes:** Often used for bundled hoses/cables, like theatrical cable for lighting and sound.  
**CE certified slings available at a rated capacity of 500 kgs @ 7:1**

“The Best Hose Suspension in the World”



MODEL  
**HB 200 ED**

For  
**Hose I.D. 2" (5 cm)**



Material:	<b>URETHANE</b>	
Length:	<b>18" / 45.7 cm</b>	
Shipping Weight:	<b>4.5 lbs / 2 kgs</b>	
Shipping Dimensions:	<b>21 x 8 x 4" / 53 x 21 x 10 cm</b>	
Sling Model:	<b>Metal "D-Ring" Sling</b>	
Sling Type:	<b>RS 16D</b>	
*Sling height:	<b>7.25" / 18.4 cm</b>	
Sling Material:	<b>UV Resistant Treated Polyester</b>	
Rated Capacity:	<b>1350 lbs/ 612 kgs @ 5:1 WLL</b>	<b>437 kgs/ 964 lbs @ 7:1 WLL</b>
Maximum Temperature:	<b>200° F / 93.3° C</b>	

\*Measured from top of the bun to the top of the sling

**Notes:** Also available with Type 4 Hook-Eye sling (Model # RS 234H) for heavy duty jobs.

(WLL for RS 234H: 2000lb / 907kgs @ 5:1 or 648kgs / 1428lbs @ 7:1)

**CE certified slings available at a rated capacity of 500 kgs @ 7:1**

**“The Best Hose Suspension in the World”**



**MODEL**  
**HB 200 SRD**  
**For**  
**Hose I.D. 2” (5 cm)**



Material:	<b>URETHANE</b>	
Length:	<b>12" / 30.5 cm</b>	
Shipping Weight:	<b>2.5 lbs / 1.1 kgs</b>	
Shipping Dimensions:	<b>13 x 5 x 3.5" / 33 x 13 x 9 cm</b>	
Sling Model:	<b>Metal "D-Ring" Sling</b>	
Sling Type:	<b>RS 16D</b>	
*Sling height:	<b>7.25" / 18.4 cm</b>	
Sling Material:	<b>UV Resistant Treated Polyester</b>	
Rated Capacity:	<b>1350 lbs/ 612 kgs @ 5:1 WLL</b>	<b>437 kgs/ 964 lbs @ 7:1 WLL</b>
Maximum Temperature:	<b>200° F / 93.3° C</b>	

\*Measured from top of the bun to the top of the sling

**Notes:** Also available with Type 4 Hook-Eye sling (Model # RS 234H) for heavy duty jobs.

(WLL for RS 234H: 2000lb / 907kgs @ 5:1 or 648kgs / 1428lbs @ 7:1)

**CE certified slings available at a rated capacity of 500 kgs @ 7:1**

“The Best Hose Suspension in the World”

**Hosebun<sup>®</sup>**

MODEL

**HB 300 H**

For

**Hose I.D. 3" (7.6 cm)**



Material:	<b>URETHANE</b>
Length:	<b>12.75" / 32.4 cm</b>
Shipping Weight:	<b>4.25 lbs / 1.9 kgs</b>
Shipping Dimensions:	<b>13 x 6 x 5" or 36 x 15 x 13 cm</b>
Sling Type:	<b>Type 4 Hook Eye</b>
Sling Model:	<b>RS 234H</b>
*Sling height: <small>*Measured from top of the bun to the top of the sling</small>	<b>14.75" / 37.5 cm</b>
Sling Material:	<b>UV Resistant Treated Polyester</b>
Rated Capacity:	<b>2000 lbs/907 kgs @ 5:1 WLL</b>
	<b>648 kgs/1429 lbs @ 7:1 WLL</b>
Maximum Temperature:	<b>200° F / 93.3° C</b>

**Notes:** Hosebun for 3" (7.6cm) hose with type 4 hook eye sling for increased strength and work safety.  
**CE certified slings available at a rated capacity of 1000 kgs @ 7:1**

“The Best Hose Suspension in the World”



MODEL

**HB 400 H**

For

**Hose I.D. 4" (10 cm)**



Material:	<b>URETHANE</b>
Length:	<b>11.5" / 28.75 cm</b>
Shipping Weight:	<b>5 lbs / 2.3 kgs</b>
Shipping Dimensions:	<b>13 x 8 x 7" or 32 x 20 x 18 cm</b>
Sling Type:	<b>Type 4 Hook Eye</b>
Sling Model:	<b>RS 234H</b>
*Sling height: <small>*Measured from top of the bun to the top of the sling</small>	<b>14.75" / 37.2 cm</b>
Sling Material:	<b>UV Resistant Treated Polyester</b>
Rated Capacity:	<b>2000 lbs/907 kgs @ 5:1 WLL</b>
	<b>648 kgs/1429 lbs @ 7:1 WLL</b>
Maximum Temperature:	<b>200° F / 93.3° C</b>

**Notes:** Hosebun for 4" (10cm) hose with type 4 hook eye sling for increased strength and work safety.  
**CE certified slings available at a rated capacity of 1000 kgs @ 7:1**

“The Best Hose Suspension in the World”



MODEL

**HB 600 H**

For

**Hose I.D. 6" (15 cm)**



Material:	<b>URETHANE</b>
Length:	<b>21.5" / 54.6 cm</b>
Shipping Weight:	<b>17 lbs / 7.7 kgs</b>
Shipping Dimensions:	<b>23 x 10 x 15"</b> or <b>57 x 23 x 31 cm</b>
Sling Type:	<b>Type 4 Hook Eye</b>
Sling Model:	<b>RS 600H</b>
*Sling height: <small>*Measured from top of the bun to the top of the sling</small>	<b>22.5" / 57.15 cm</b>
Sling Material:	<b>UV Resistant Treated Polyester</b>
Rated Capacity:	<b>8000 lbs / 3629 kgs @ 5:1 WLL</b>
	<b>2590 kgs / 5700 lbs @ 7:1 WLL</b>
Maximum Temperature:	<b>200° F / 93.3° C</b>

**Notes:** Use Heat Wrap to extend temperature capacity up to 1100°F / 593°C (Model# HW600).  
For 5" ID hoses, please ask us about our hosebun liners to ensure a secure fit. (Model# HBL 600).  
**CE certified slings available at a rated capacity of 3000 kgs @ 7:1**

**“The Best Hose Suspension in the World”**



**MODEL**

**HB 800 H**

**For**

**Hose I.D. 8” (20 cm)**



Material:	<b>URETHANE</b>
Length:	<b>30.5” / 77.5 cm</b>
Shipping Weight:	<b>37 lbs / 16.8 kgs</b>
Shipping Dimensions:	<b>32 x 12 x 15” or 81 x 31 x 38 cm</b>
Sling Type:	<b>Type 4 Hook Eye</b>
Sling Model:	<b>RS 800H</b>
*Sling height: <small>*Measured from top of the bun to the top of the sling</small>	<b>18” / 45.7 cm</b>
Sling Material:	<b>UV Resistant Treated Polyester</b>
Rated Capacity:	<b>12000 lbs / 5443 kgs @ 5:1 WLL</b>
	<b>3888 kgs / 8570 lbs @ 7:1 WLL</b>
Maximum Temperature:	<b>200° F / 93.3° C</b>

**Notes:** Use Heat Wrap to extend temperature capacity up to 1100°F / 593°C (Model# HW800).  
**CE certified slings available at a rated capacity of 4000 kgs @ 7:1 WLL**

**“The Best Hose Suspension in the World”**



**MODEL**

**HB 1000 H**

**For**

**Hose I.D. 10” (25 cm)**



Material:	<b>URETHANE</b>
Length:	<b>40.75" / 103.5 cm</b>
Shipping Weight:	<b>62 lbs / 28 kgs</b>
Shipping Dimensions:	<b>42 x 15 x 18" or 106 x 37.5 x 46 cm</b>
Sling Type:	<b>Type 4 Hook Eye</b>
Sling Model:	<b>RS 1000H</b>
*Sling height: <small>*Measured from top of the bun to the top of the sling</small>	<b>19.25" / 48.90 cm</b>
Sling Material:	<b>UV Resistant Treated Polyester</b>
Rated Capacity:	<b>15000 lbs / 6803 kgs @ 5:1 WLL</b>
	<b>4860 kgs / 10700 lbs @ 7:1 WLL</b>
Maximum Temperature:	<b>200° F / 93.3° C</b>

**Notes:** Use Heat Wrap to extend temperature capacity up to 1100°F / 593°C (Model# HW 1000).  
**CE certified slings available at a rated capacity of 5000 kgs @ 7:1 WLL**

“The Best Hose Suspension in the World”



MODEL

**HB 1200 H**

For

**Hose I.D. 12” (30 cm)**



Material:	<b>URETHANE</b>
Length:	<b>40.75" / 103.5 cm</b>
Shipping Weight:	<b>62 lbs / 28 kgs</b>
Shipping Dimensions:	<b>42 x 15 x 18"</b> or <b>106 x 37.5 x 46 cm</b>
Sling Type:	<b>Type 4 Hook Eye</b>
Sling Model:	<b>RS 1200H</b>
*Sling height: <small>*Measured from top of the bun to the top of the sling</small>	<b>23.25" / 59.1 cm</b>
Sling Material:	<b>UV Resistant Treated Polyester</b>
Rated Capacity:	<b>15000 lbs / 6803 kgs</b> <b>@ 5:1 WLL</b>
	<b>4860 kgs / 10700 lbs</b> <b>@ 7:1 WLL</b>
Maximum Temperature:	<b>200° F / 93.3° C</b>

**Notes:** Same mold as the HB 1000H but with a longer sling to accommodate a 12" (30cm) I.D. hose. Use Heat Wrap to extend temperature capacity up to 1100°F / 593°C (Model# HW 1200).  
**CE certified slings available at a rated capacity of 5000 kgs @ 7:1 WLL**

“The Best Hose Suspension in the World”



MODEL

**HB 1200 H**

For

**Hose I.D. 12” (30 cm)**



Material:	<b>URETHANE</b>
Length:	<b>40.75" / 103.5 cm</b>
Shipping Weight:	<b>62 lbs / 28 kgs</b>
Shipping Dimensions:	<b>42 x 15 x 18"</b> or <b>106 x 37.5 x 46 cm</b>
Sling Type:	<b>Type 4 Hook Eye</b>
Sling Model:	<b>RS 1000H</b>
*Sling height: <small>*Measured from top of the bun to the top of the sling</small>	<b>23.25" / 59.1 cm</b>
Sling Material:	<b>UV Resistant Treated Polyester</b>
Rated Capacity:	<b>15000 lbs / 6803 kgs @ 5:1 WLL</b>
	<b>4860 kgs / 10700 lbs @ 7:1 WLL</b>
Maximum Temperature:	<b>200° F / 93.3° C</b>

**Notes:** Same mold as the HB 1000H but with a longer sling to accommodate a 12" (30cm) I.D. hose. Use Heat Wrap to extend temperature capacity up to 1100°F / 593°C (Model# HW 1200).  
**CE certified slings available at a rated capacity of 5000 kgs @ 7:1 WLL**