

## Rubber Sheeting Selection



### Neoprene Rubber

Colour :	Black
Hardness:	70°
Elongation at break :	300%
Tensile Strength :	5 MPa
Temperature range :	-20 °C to +110°C
Comments:	Good mechanical properties Oil and weather resistant



### Insertion Rubber (fabric reinforcement layer for increased strength)

Colour :	Black
Hardness:	65°
Elongation at break :	300%
Tensile Strength :	5 MPa
Temperature range :	-20 °C to +110°C
Comments:	Good mechanical properties Fair resistance to oil/acid. Good weather resistance



### Closed Cell Sponge Rubber (adhesive back)

Colour :	Black
Hardness:	7-12 Duro
Temperature range :	-30 °C to +80°C
Comments:	Offers excellent sealing performance, providing acid, flame & oil resistance. Shock absorption/ Impact dampening

### Stock and Services

Thicknesses:	1/16" – 1"
Width:	55"
Sold per:	Linear ft or ft <sup>2</sup>
Labour charge:	Cutting and/or sticking Case by case basis

**IRP Fire & Safety Limited**  
Hose Management Services  
119 Boundary Road,  
San Juan, Trinidad W.I.  
Email: [csr.fse@irpltd.com](mailto:csr.fse@irpltd.com)  
Website: [www.irpltd.com](http://www.irpltd.com)  
Phone: 674-0693/4